

Reflecta-Floor 500 Plus[™]

<mark>green</mark>guide Technical Data Sheet



Phone: 1300 308 165 Fax: 1300 308 164 Web: gibuildingsciences.com.au

greenguide Technical Data Sheet



Reflecta- Floor 500 Plus™ Product Data

| Product Code | RCF500 |
|--------------------------|---|
| Silver Side Emittance | 0.03 |
| Antiglare Side Emittance | 0.05 |
| Roll Size | 0.5M X 20M x 3Rolls (30M ²) |
| Product Thickness | 5.5MM (±0.5MM) |
| Roll Weight | 13.2KG (±7%) |

Total R – Values (m²K/W)

| Heat Flow | INWARD | OUTWARD |
|-----------|--------|---------|
| Floor | 2.0 | 3.8 |

* Include floor covering and underlay – R0.3

** For specific calculation details please contact GI Building Sciences

Product Testing

| Thermal Performance | ASTM C518 | |
|-----------------------------|---------------------------|--|
| Material Thermal Resistance | 0.12 (M ² K/W) | |
| Flammability | AS 1530.2 | |
| Ignitability | AS/NZS 1530.3 | |
| Spread of Flame | AS/NZS 1530.3 | |
| Heat Evolved | AS/NZS 1530.3 | |
| Smoke Developed | AS/NZS 1530.3 | |
| Textile Testing | EXTRA HEAVY DUTY | |
| Dry Delamination | AS/NZS 4201.1 | |
| Wet Delamination | AS/NZS 4201.2 | |
| Shrinkage | AS/NZS 4201.3 | |
| Water Penetration | AS/NZS 4201.4 | |
| Water Absorbency | AS/NZS 4201.6 | |
| Water Vapour Transmission | ASTM E96 | |
| Edge Tear | AS 4200.1 | |
| Surface Corrosion | AS/NZS 4859.1 Appendix I | |
| Electrical Conductivity | Conductive | |
| | ISO 354 | |
| Acoustic | AS ISO 11654 | |
| | AS 1191 | |

Please note that products are to be stored standing upright and on pallets not more than two high. Product warranty is voided for any product stored horizontally resulting in squeeze or crush. Returns of product displaying effects of deformation due to incorrect storage practices will not be accepted.









